



The MSDS format adheres to the standards and regulatory requirements of the United States and may not meet regulatory requirements in other countries.

DuPont  
Material Safety Data Sheet

Page 1

-----  
"StoneTech" Professional Impregnator Pro(TM) Sealer  
6458CR Revised 5-JUN-2006  
-----

-----  
CHEMICAL PRODUCT/COMPANY IDENTIFICATION  
-----

Company Identification

MANUFACTURER/DISTRIBUTOR

StoneTech Professional, Inc.  
370 North Wiget Lane, Suite 200  
Walnut Creek, CA 94598

PHONE NUMBERS

Product Information : 800-441-7515/Outside US: 302-774-1000  
Transport Emergency : CHEMTREC: 800-424-9300/Outside US:  
703-527-3887  
Medical Emergency : 800-441-3637/Outside US: 302-774-1000

-----  
COMPOSITION/INFORMATION ON INGREDIENTS  
-----

# Components

Material	CAS Number	%
Fluorinated Acrylic Copolymer		
Petroleum Distillate	64742-48-9	
Proprietary Silicone Resin		
Aliphatic Hydrocarbons	68551-16-6	

-----  
HAZARDS IDENTIFICATION  
-----

Potential Health Effects

Inhalation may cause respiratory irritation with headache, dizziness, nausea, or unconsciousness.

Skin contact may cause mild irritation.

Eye contact may cause mild irritation.

Ingestion may irritate stomach and intestines. May be aspirated into lungs if swallowed, resulting in pulmonary edema and chemical pneumonitis. Harmful or fatal if swallowed.

Carcinogenicity Information

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.

-----  
FIRST AID MEASURES  
-----

## First Aid

## INHALATION

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

## SKIN CONTACT

Flush skin with water after contact. Wash contaminated clothing before reuse.

## EYE CONTACT

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

## INGESTION

If swallowed, do not induce vomiting. DO NOT GIVE ANYTHING TO DRINK. Call a physician immediately. Never give anything by mouth to an unconscious person.

-----  
FIRE FIGHTING MEASURES  
-----

## Flammable Properties

Flash Point : 120 F (49 C)  
Method : Closed Cup.

Combustible liquid.

## Extinguishing Media

Water, Foam, Dry Chemical, CO2.

## Fire Fighting Instructions

Evacuate personnel to a safe area. Wear self-contained breathing apparatus (SCBA) and full protective equipment.

-----  
ACCIDENTAL RELEASE MEASURES  
-----

## Safeguards (Personnel)

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

## (ACCIDENTAL RELEASE MEASURES - Continued)

Wear self-contained breathing apparatus (SCBA) and full protective gear.

## Initial Containment

Dike spill.

## Spill Clean Up

Soak up with sawdust, sand, oil dry or other absorbent material.  
Shovel or sweep up.

-----  
HANDLING AND STORAGE  
-----

## Handling (Personnel)

Avoid inhalation. Avoid contact with eyes, skin or clothing.  
Wash thoroughly after handling. Wash clothing after use.

## Handling (Physical Aspects)

Keep container tightly closed.

## Storage

Store in a cool, dry place.

-----  
EXPOSURE CONTROLS/PERSONAL PROTECTION  
-----

## Engineering Controls

Use only with adequate ventilation.

## Personal Protective Equipment

## EYE/FACE PROTECTION

Wear safety glasses, or where splash potential exists wear chemical splash goggles.

## RESPIRATORS

Where the potential exists for airborne exposure, wear NIOSH approved respiratory protection.

## PROTECTIVE CLOTHING

Where there is potential for skin contact, have available and wear as appropriate impervious gloves, apron or smock.

## Exposure Guidelines

## Applicable Exposure Limits

## Petroleum Distillate

PEL (OSHA) : None Established  
TLV (ACGIH) : None Established  
AEL \* (DuPont) : 100 ppm, 8 Hr. TWA

\* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

-----  
PHYSICAL AND CHEMICAL PROPERTIES  
-----

## Physical Data

Evaporation Rate : <1 (Butyl Acetate=1.0)  
Solubility in Water : Negligible  
Boiling Point : 340 F (171 C)  
Odor : Hydrocarbon (mild).  
Form : Liquid.  
Color : Colorless.  
Specific Gravity : 0.8 25 C (77 F)

-----  
STABILITY AND REACTIVITY  
-----

## Chemical Stability

Stable.

## Incompatibility with Other Materials

Incompatible with oxygen, strong oxidizing agents.

## Decomposition

Thermal decomposition may produce carbon monoxide, carbon dioxide, hydrogen fluoride and silicon dioxide.

## Polymerization

Polymerization will not occur.

-----  
DISPOSAL CONSIDERATIONS  
-----

## Waste Disposal

Treatment, storage, transportation, and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations.

-----  
TRANSPORTATION INFORMATION  
-----

## Shipping Information

DOT: Not Regulated by DOT in packages with a capacity of less than 119 gallons.

## IMDG:

For 5 gal. and 55 gal. package:

Proper Shipping Name : Hydrocarbon Liquid, N.O.S.  
Hazard Class : 3  
UN Number : 3295  
Packing Group : III  
Label : Flammable Liquid

For 2 Oz., 1 Pint, 1 Quart, and 1 Gal.:

Proper Shipping Name : Hydrocarbon Liquid, N.O.S.  
Hazard Class : 3  
UN Number : 3295  
Packing Group : III  
Label : Flammable Liquid  
Special Instructions : Limited Quantity

## IATA:

For 5 gal. and 55 gal. package:

Proper Shipping Name : Hydrocarbon Liquid, N.O.S.  
Hazard Class : 3  
UN Number : 3295  
Packing Group : III  
Label : Flammable Liquid

For 1 Quart and 1 Gal.:

Proper Shipping Name : Hydrocarbon Liquid, N.O.S.  
Hazard Class : 3  
UN Number : 3295  
Packing Group : III  
Label : Flammable Liquid  
Special Instructions : Limited Quantity

For 2 Oz. and 1 Pint:

Proper Shipping Name : Consumer Commodity  
Hazard Class : 9  
UN Number : ID 8000  
Label : Miscellaneous

-----  
REGULATORY INFORMATION  
-----

U.S. Federal Regulations

TSCA Inventory Status : In compliance with TSCA Inventory requirements for commercial purposes.

-----  
The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

# Indicates updated section.

This information is based upon technical information believed to be reliable. It is subject to revision as additional knowledge and experience is gained.

End of MSDS